

WHAT IS CLAIMED IS:

1. A method for generating a service level agreement delay value for a network, comprising:

- 5 receiving a set of network delay samples;
- generating a path delay for a path through the network over a specified time period using the set of network delay samples;
- generating a confidence interval for the path delay using the specified time period, the set of network delay samples, and a confidence level; and
- 10 generating the service level agreement delay value using the path delay and the confidence interval.

15 2. The method of claim 1, further comprising applying a data sieve to the set of network delay samples.

3. The method of claim 1 wherein the specified time period is a path busy period for the path.

20 4. The method of claim 3, wherein determining a path busy period further includes:

- receiving a time period;
- generating a first path delay over the time period at a first time point using the set of network delay samples;
- 25 generating a second path delay over the time period at a second time point using the set of network delay samples;
- and
- generating the path busy period by comparing the first path delay to the second path delay.
- 30

5. The method of claim 4, wherein generating a path delay at a time point further includes:

"1035306" 110304

determining a set of trunks included in the path;
for each trunk in the set of trunks, performing the
following:

5 generating a trunk delay for a trunk over the
time period at the time point using the set of network
delay samples; and
 adding the trunk delay to the path delay.

6. The method of claim 1, wherein generating a confidence
10 interval for the path delay further includes:

 determining a set of trunks included in the path;
 generating a set of trunk delay standard deviations
from the set of trunks for the specified time period using
the set of network delay samples;
15 generating a path delay standard deviation using the
set of trunk delay standard deviations; and
 generating the confidence interval using the path
delay standard deviation and the confidence level.

20 7. A method for monitoring a network, comprising:
 receiving a set of network delay samples;
 generating a path busy period for a path through the
network using the set of network delay samples;
 generating a path delay for the path using the path
25 busy period and the set of network delay samples;
 generating a path delay standard deviation using the
path delay, path busy period, and the set of network delay
samples;
 generating a coefficient of variation for the path
30 delay using the path delay and the path standard deviation;
and
 generating an alert by comparing the coefficient of
variation to a threshold coefficient of variation value.

8. The method of claim 7, further comprising applying a data sieve to the set of network delay samples.

5 9. The method of claim 7, wherein generating a path busy period further includes:

receiving a time period;

generating a first path delay over the time period at a first time point using the set of network delay samples;

10 generating a second path delay over the time period at a second time point using the set of network delay samples; and

generating the path busy period by comparing the first path delay to the second path delay.

15 10. The method of claim 9, wherein generating a path delay at a time point further includes:

determining a set of trunks included in the path;

20 for each trunk in the set of trunks, performing the following:

generating a trunk delay over the time period at the time point using the set of network delay samples; and

adding the trunk delay to the path delay.

25 11. The method of claim 7, wherein generating a path delay standard deviation further includes:

determining a set of trunks included in the path;

30 generating a set of trunk delay standard deviations from the set of trunks for the path busy period using the set of network delay samples; and

generating a path delay standard deviation using the set of trunk delay standard deviations.

10035806 "410801

12. A method for monitoring a network, comprising:

receiving a set of network delay samples;

5 generating a path busy period for a path through the network using the set of network delay samples;

generating a confidence interval for the path using the path busy period, the set of network delay samples, and a confidence level;

10 generating a busy period path delay for the path using the path busy period, the set of network delay samples, and the confidence interval; and

comparing the busy period path delay to a busy period path delay baseline including a plurality of previously generated busy period path delays.

15

13. The method of claim 12, further comprising applying a data sieve to the set of network delay samples.

14. The method of claim 12, wherein generating a path busy period further includes:

receiving a time period;

generating a first path delay over the time period at a first time point using the set of network delay samples;

25 generating a second path delay over the time period at a second time point using the set of network delay samples; and

generating the path busy period by comparing the first path delay to the second path delay.

30 15. The method of claim 14, wherein generating a path delay at a time point further includes:

determining a set of trunks included in the path;

for each trunk in the set of trunks, performing the

following:

generating a trunk delay over the time period at
the time point using the set of network delay samples;
and

5 adding the trunk delay to the path delay.

16. The method of claim 12, wherein generating a confidence interval for the path further includes:

determining a set of trunks included in the path;

10 generating a set of trunk delay standard deviations from the set of trunks for the path busy period using the set of network delay samples;

generating a path delay standard deviation using the set of trunk delay standard deviations; and

15 generating the confidence interval using the path delay standard deviation and the confidence level.

17. A method for monitoring a network, comprising:

receiving a set of network delay samples;

20 generating a trunk busy period for a trunk in the network using the set of network delay samples;

generating a trunk delay for the trunk using the trunk busy period and the set of network delay samples;

25 generating a trunk delay standard deviation using the trunk delay, trunk busy period, and the set of network delay samples;

generating a coefficient of variation for the trunk using the trunk delay and the trunk standard deviation; and

30 generating an alert by comparing the coefficient of variation to a threshold coefficient of variation value.

18. The method of claim 17, further comprising applying a data sieve to the set of network delay samples.

19. The method of claim 17, wherein generating a trunk busy period further includes:

receiving a time period;

5 generating a first trunk delay over the time period at a first time point using the set of network delay samples;

generating a second trunk delay over the time period at a second time point using the set of network delay samples; and

10 generating the trunk busy period by comparing the first trunk delay to the second trunk delay.

20. A method for monitoring a network, comprising:

receiving a set of network delay samples;

15 generating a trunk busy period for a trunk included in the network using the set of network delay samples;

generating a confidence interval for the trunk using the trunk busy period, the set of network delay samples, and a confidence level;

20 generating a busy period trunk delay for the trunk using the trunk busy period, the set of network delay samples, and the confidence interval; and

25 comparing the busy period trunk delay to a busy period trunk delay baseline including a plurality of previously generated busy period trunk delays.

21. The method of claim 20, further comprising applying a data sieve to the set of network delay samples.

30 22. The method of claim 20, wherein generating a trunk busy period further includes:

receiving a time period;

generating a first trunk delay over the time period at

10035606-110801

a first time point using the set of network delay samples;
 generating a second trunk delay over the time period
 at a second time point using the set of network delay
 samples; and

5 generating the trunk busy period by comparing the
 first trunk delay to the second trunk delay.

23. A method for generating a service level agreement delay
 value for a network, comprising:

10 receiving a set of network delay samples;
 applying a data sieve to the set of network delay
 samples;

 generating a path busy period for a path through the
 network by performing the following:

15 receiving a time period,
 generating a first path delay over the time
 period at a first time point using the set of network
 delay samples,

 generating a second path delay over the time
 20 period at a second time point using the set of network
 delay samples, and

 generating the path busy period by comparing the
 first path delay to the second path delay;

 generating a confidence interval for the path delay by
 25 performing the following:

 determining a set of trunks included in the path;
 generating a set of trunk delay standard
 deviations from the set of trunks for the path busy
 period using the set of network delay samples,

30 generating a path delay standard deviation using
 the set of trunk delay standard deviations, and

 generating the confidence interval using the path
 delay standard deviation and the confidence level; and

generating the service level agreement delay value
using the path delay and the confidence interval.

24. The method of claim 23, wherein generating a path delay at
a time point further includes:

determining a set of trunks included in the path;
for each trunk in the set of trunks, performing the
following:

generating a trunk delay for a trunk over the
time period at the time point using the set of network
delay samples; and

adding the trunk delay to the path delay.

25. A method for monitoring a network, comprising:

receiving a set of network delay samples;
applying a data sieve to the set of network delay
samples;

generating a path busy period for a path through the
network by performing the following:

receiving a time period,
generating a first path delay over the time
period at a first time point using the set of network
delay samples,

generating a second path delay over the time
period at a second time point using the set of network
delay samples, and

generating the path busy period by comparing the
first path delay to the second path delay;

generating a confidence interval for the path delay by
performing the following:

determining a set of trunks included in the path;
generating a set of trunk delay standard
deviations from the set of trunks for path busy period

using the set of network delay samples,
 generating a path delay standard deviation using
 the set of trunk delay standard deviations, and
 generating the confidence interval using the path
 5 delay standard deviation and the confidence level;
 generating a coefficient of variation for the path
 delay using the path delay and the path standard deviation;
 and
 generating an alert by comparing the coefficient of
 10 variation to a threshold coefficient of variation value.

26. The method of claim 25, wherein generating a path delay at
 a time point further includes:

determining a set of trunks included in the path;
 15 for each trunk in the set of trunks, performing the
 following:
 generating a trunk delay over the time period at
 the time point using the set of network delay samples;
 and
 20 adding the trunk delay to the path delay.

27. A data processing apparatus adapted for generating a service
 level agreement delay value for a network, comprising:

a processor; and
 25 a memory operably coupled to the processor and having
 program instructions stored therein, the processor being
 operable to execute the program instructions, the program
 instructions including:
 receiving a set of network delay samples;
 30 generating a path delay for a path through the
 network over a specified time period using the set of
 network delay samples;
 generating a confidence interval for the path

delay using the path delay, the specified time period,
the set of network delay samples, and a confidence
level; and

5 generating the service level agreement delay
value using the path delay and the confidence
interval.

28. The data processing apparatus of claim 27, the program
instructions further including applying a data sieve to the set
10 of network delay samples.

29. The data processing apparatus of claim 27 wherein the
specified time period is a path busy period for the path.

15 30. The data processing apparatus of claim 29, wherein the
program instructions for determining a path busy period further
include:

receiving a time period;

20 generating a first path delay over the time period at
a first time point using the set of network delay samples;

 generating a second path delay over the time period at
a second time point using the set of network delay samples;
and

25 generating the path busy period by comparing the first
path delay to the second path delay.

31. The data processing apparatus of claim 30, wherein the
program instructions for generating a path delay at a time point
further include:

30 determining a set of trunks included in the path;

 for each trunk in the set of trunks, performing the
following:

 generating a trunk delay for a trunk over the

time period at the time point using the set of network delay samples; and

adding the trunk delay to the path delay.

- 5 32. The data processing apparatus of claim 27, wherein generating a confidence interval for the path delay further includes:

determining a set of trunks included in the path;

generating a set of trunk delay standard deviations
10 from the set of trunks for the specified time period using the set of network delay samples;

generating a path delay standard deviation using the set of trunk delay standard deviations; and

generating the confidence interval using the path
15 delay standard deviation and the confidence level.

33. A data processing apparatus adapted for monitoring a network, comprising:

a processor; and

20 a memory operably coupled to the processor and having program instructions stored therein, the processor being operable to execute the program instructions, the program instructions including:

receiving a set of network delay samples;

25 generating a path busy period for a path through the network using the set of network delay samples;

generating a path delay for the path using the path busy period and the set of network delay samples;

30 generating a path delay standard deviation using the path delay, path busy period, and the set of network delay samples;

generating a coefficient of variation for the path delay using the path delay and the path standard

deviation; and

generating an alert by comparing the coefficient of variation to a threshold coefficient of variation value.

5

34. The data processing apparatus of claim 33, the program instructions further including applying a data sieve to the set of network delay samples.

10 35. The data processing apparatus of claim 33, wherein the program instructions for generating a path busy period further include:

receiving a time period;

15

generating a first path delay over the time period at a first time point using the set of network delay samples;

generating a second path delay over the time period at a second time point using the set of network delay samples; and

20

generating the path busy period by comparing the first path delay to the second path delay.

36. The data processing apparatus of claim 35, wherein the program instructions for generating a path delay at a time point further include:

25

determining a set of trunks included in the path;

for each trunk in the set of trunks, performing the following:

generating a trunk delay over the time period at the time point using the set of network delay samples;

30

and

adding the trunk delay to the path delay.

37. The data processing apparatus of claim 36, wherein the

10035806-1103601

program instructions for generating a path delay standard deviation further include:

determining a set of trunks included in the path;

generating a set of trunk delay standard deviations

5 from the set of trunks for the path busy period using the set of network delay samples; and

generating a path delay standard deviation using the set of trunk delay standard deviations.

10 38. A data processing apparatus adapted for monitoring a network, comprising:

a processor; and

a memory operably coupled to the processor and having program instructions stored therein, the processor being operable to execute the program instructions, the program instructions including:

receiving a set of network delay samples;

generating a path busy period for a path through the network using the set of network delay samples;

20 generating a confidence interval for the path using the path busy period, the set of network delay samples, and a confidence level;

25 generating a busy period path delay for the path using the path busy period, the set of network delay samples, and the confidence interval; and

comparing the busy period path delay to a busy period path delay baseline including a plurality of previously generated busy period path delays.

30 39. The data processing apparatus of claim 38, the program instructions further including applying a data sieve to the set of network delay samples.

40. The data processing apparatus of claim 38, wherein the program instructions for generating a path busy period further include:

- receiving a time period;
- 5 generating a first path delay over the time period at a first time point using the set of network delay samples;
- generating a second path delay over the time period at a second time point using the set of network delay samples;
- and
- 10 generating the path busy period by comparing the first path delay to the second path delay.

41. The data processing apparatus of claim 40, wherein the program instructions for generating a path delay at a time point further include:

- determining a set of trunks included in the path;
- for each trunk in the set of trunks, performing the following:
- generating a trunk delay over the time period at
- 20 the time point using the set of network delay samples;
- and
- adding the trunk delay to the path delay.

42. The data processing apparatus of claim 38, wherein the program instructions for generating a confidence interval for the path further include:

- determining a set of trunks included in the path;
- generating a set of trunk delay standard deviations from the set of trunks for the path busy period using the
- 30 set of network delay samples;
- generating a path delay standard deviation using the set of trunk delay standard deviations; and
- generating the confidence interval using the path

10035806 110801

delay standard deviation and the confidence level.

43. A data processing apparatus adapted for monitoring a network, comprising:

- 5 a processor; and
- a memory operably coupled to the processor and having program instructions stored therein, the processor being operable to execute the program instructions, the program instructions including:
 - 10 receiving a set of network delay samples;
 - generating a trunk busy period for a trunk in the network using the set of network delay samples;
 - generating a trunk delay for the trunk using the trunk busy period and the set of network delay samples;
 - 15 generating a trunk delay standard deviation using the trunk delay, trunk busy period, and the set of network delay samples;
 - generating a coefficient of variation for the trunk using the trunk delay and the trunk standard deviation; and
 - 20 generating an alert by comparing the coefficient of variation to a threshold coefficient of variation value.

25 44. The data processing apparatus of claim 43, the program instructions further including applying a data sieve to the set of network delay samples.

30 45. The data processing apparatus of claim 43, wherein the program instructions for generating a trunk busy period further include:

- receiving a time period;

generating a first trunk delay over the time period at a first time point using the set of network delay samples;

generating a second trunk delay over the time period at a second time point using the set of network delay

5 samples; and

generating the trunk busy period by comparing the first trunk delay to the second trunk delay.

46. A data processing apparatus adapted for monitoring a
10 network, comprising:

a processor; and

a memory operably coupled to the processor and having program instructions stored therein, the processor being operable to execute the program instructions, the program
15 instructions including:

receiving a set of network delay samples;

generating a trunk busy period for a trunk included in the network using the set of network delay samples;

20 generating a confidence interval for the trunk using the trunk busy period, the set of network delay samples, and a confidence level;

generating a busy period trunk delay for the trunk using the trunk busy period, the set of network delay samples, and the confidence interval; and
25

comparing the busy period trunk delay to a busy period trunk delay baseline including a plurality of previously generated busy period trunk delays.

30 47. The data processing apparatus of claim 45, wherein the program instructions for generating a trunk busy period further includes:

receiving a time period;

generating a first trunk delay over the time period at
a first time point using the set of network delay samples;

generating a second trunk delay over the time period
at a second time point using the set of network delay
samples; and

generating the trunk busy period by comparing the
first trunk delay to the second trunk delay.

48. A data processing apparatus adapted for generating a service
level agreement delay value, comprising:

a processor; and

a memory operably coupled to the processor and having
program instructions stored therein, the processor being
operable to execute the program instructions, the program
instructions including:

receiving a set of network delay samples;

applying a data sieve to the set of network delay
samples;

generating a path busy period for a path through
the network by performing the following:

receiving a time period,

generating a first path delay over the time
period at a first time point using the set of
network delay samples,

generating a second path delay over the time
period at a second time point using the set of
network delay samples, and

generating the path busy period by comparing
the first path delay to the second path delay;

generating a confidence interval for the path
delay by performing the following:

determining a set of trunks included in the
path;

generating a set of trunk delay standard deviations from the set of trunks for the path busy period using the set of network delay samples,

5 generating a path delay standard deviation using the set of trunk delay standard deviations, and

10 generating the confidence interval using the path delay standard deviation and the confidence level; and

generating the service level agreement delay value using the path delay and the confidence interval.

15 49. The data processing apparatus of claim 48, wherein the program instructions for generating a path delay at a time point further include:

determining a set of trunks included in the path;

for each trunk in the set of trunks, performing the

20 following:

generating a trunk delay for a trunk over the time period at the time point using the set of network delay samples; and

adding the trunk delay to the path delay.

25

50. A data processing apparatus adapted for monitoring a network, comprising:

a processor; and

a memory operably coupled to the processor and having

30 program instructions stored therein, the processor being operable to execute the program instructions, the program instructions including:

receiving a set of network delay samples;

10035306-110301

applying a data sieve to the set of network delay samples;

generating a path busy period for a path through the network by performing the following:

5 receiving a time period,

generating a first path delay over the time period at a first time point using the set of network delay samples,

10 generating a second path delay over the time period at a second time point using the set of network delay samples, and

generating the path busy period by comparing the first path delay to the second path delay;

15 generating a confidence interval for the path delay by performing the following:

determining a set of trunks included in the path,

20 generating a set of trunk delay standard deviations from the set of trunks for path busy period using the set of network delay samples,

generating a path delay standard deviation using the set of trunk delay standard deviations, and

25 generating the confidence interval using the path delay standard deviation and the confidence level;

generating a coefficient of variation for the path delay using the path delay and the path standard deviation; and

30 generating an alert by comparing the coefficient of variation to a threshold coefficient of variation value.

47240/FLC/I281

51. The data processing apparatus of claim 50, wherein the program instructions for generating a path delay at a time point further include:

determining a set of trunks included in the path;

5 for each trunk in the set of trunks, performing the following:

generating a trunk delay over the time period at the time point using the set of network delay samples; and

10 adding the trunk delay to the path delay.

52. A computer readable media embodying program instructions for execution by a data processing apparatus, the program instructions adapting a data processing apparatus for generating a service level agreement delay value, the program instructions comprising:

receiving a set of network delay samples;

applying a data sieve to the set of network delay samples;

20 generating a path busy period for a path through the network by performing the following:

receiving a time period,

generating a first path delay over the time period at a first time point using the set of network delay samples,

25 generating a second path delay over the time period at a second time point using the set of network delay samples, and

30 generating the path busy period by comparing the first path delay to the second path delay;

generating a confidence interval for the path delay by performing the following:

determining a set of trunks included in the path;

10035306-140304

generating a set of trunk delay standard deviations from the set of trunks for the path busy period using the set of network delay samples,
generating a path delay standard deviation using
5 the set of trunk delay standard deviations, and
generating the confidence interval using the path delay standard deviation and the confidence level; and
generating the service level agreement delay value using the path delay and the confidence interval.

10 53. The computer readable media of claim 52, wherein the program instructions for generating a path delay at a time point further include:

determining a set of trunks included in the path;
15 for each trunk in the set of trunks, performing the following:
generating a trunk delay for a trunk over the time period at the time point using the set of network delay samples; and
20 adding the trunk delay to the path delay.

54. A computer readable media embodying program instructions for execution by a data processing apparatus, the program instructions adapting a data processing apparatus for monitoring
25 a network, the program instructions comprising:

receiving a set of network delay samples;
applying a data sieve to the set of network delay samples;
generating a path busy period for a path through the
30 network by performing the following:
receiving a time period,
generating a first path delay over the time period at a first time point using the set of network

delay samples,

generating a second path delay over the time period at a second time point using the set of network delay samples, and

5 generating the path busy period by comparing the first path delay to the second path delay;

generating a confidence interval for the path delay by performing the following:

determining a set of trunks included in the path,

10 generating a set of trunk delay standard deviations from the set of trunks for path busy period using the set of network delay samples,

generating a path delay standard deviation using the set of trunk delay standard deviations, and

15 generating the confidence interval using the path delay standard deviation and the confidence level;

generating a coefficient of variation for the path delay using the path delay and the path standard deviation; and

20 generating an alert by comparing the coefficient of variation to a threshold coefficient of variation value.

55. The computer readable media of claim 54, wherein the program instructions for generating a path delay at a time point further include:

determining a set of trunks included in the path;

for each trunk in the set of trunks, performing the following:

30 generating a trunk delay over the time period at the time point using the set of network delay samples; and

adding the trunk delay to the path delay.